

Service Manual

JS 200W

PUBLISHED BY THE TECHNICAL PUBLICATIONS DEPARTMENT OF JCB SERVICE: © ROCESTER, STAFFORDSHIRE, ST14 5LS, ENGLAND Tel. ROCESTER (01889) 590312 PRINTED IN ENGLAND

> Publication No. 9803/6320 Issue 2

General Information	1
Care & Safety	2
Routine Maintenance	3
Attachments	Α
Body & Framework	В
Electrics	С
Controls	D
Hydraulics	Е
Transmission	F
Brakes	G
Engine	Κ

Introduction

This publication is designed for the benefit of JCB Distributor Service Engineers who are receiving, or have received, training by JCB Technical Training Department.

These personnel should have a sound knowledge of workshop practice, safety procedures, and general techniques associated with the maintenance and repair of hydraulic earthmoving equipment.

Renewal of oil seals, gaskets, etc., and any component showing obvious signs of wear or damage is expected as a matter of course. It is expected that components will be cleaned and lubricated where appropriate, and that any opened hose or pipe connections will be blanked to prevent excessive loss of hydraulic fluid and ingress of dirt. Finally, please remember above all else

SAFETY MUST COME FIRST!

The manual is compiled in sections, the first three are numbered and contain information as follows:

- 1 = General Information includes torque settings and service tools.
- 2 = Care & Safety includes warnings and cautions pertinent to aspects of workshop procedures etc.
- 3 = Routine Maintenance includes service schedules and recommended lubricants for the whole machine.

The remaining sections are alphabetically coded and deal with Dismantling, Overhaul etc. of specific components, for example:

- A = Optional Equipment
- B = Body & Framework ...etc

The page numbering in each alphabetically coded section is not continuous. This allows for the insertion of new items in later issues of the manual.

Section contents, technical data, circuit descriptions, operation descriptions etc. are inserted at the beginning of each alphabetically coded section.

All sections are listed on the front cover; tabbed divider cards align directly with individual sections on the front cover for rapid reference.

Page cross references are generally made by presenting the subject title printed in bold, followed by the title of the section containing the subject. For example:

"24 If the axle is still on the machine, fit the brake calipers (see Brake Caliper Removal and Replacement, Section G)."

Note: If only the subject title in bold is given, i.e. no section title, the cross reference is to another part of the same section.

Use the contents list at the beginning of each section to find the exact page number.

Where a torque setting is given as a single figure it may be varied by plus or minus 3%. Torque figures indicated are for dry threads, hence for lubricated threads may be reduced by one third.

'Left Hand' and 'Right Hand' are as viewed from the rear of the machine facing forwards.

i

		- 2	

Contents	Page No.
Machine and Axle Identification	1 - 1
Torque Settings	2 - 1
Service Tools Body and Framework (Section B) Electrics (Section C) Hydraulics (Section E) Transmission (Section F)	4 - 1 5 - 1 6 - 1 7 - 1
Sealing and Retaining Compounds	9 - 1

1 - 1

Machine and Axle Identification

1 - 1

Your machine has a Data Plate, located inside the cab, as shown at A. The machine serial number is inscribed at B and the engine number has two serial number plates C and D.

Tier 2 engine number plate is positioned at E.

If the engine is replaced by a new one, the data plate serial number will be wrong. Either stamp the new number on the plate or stamp out the old one. This will prevent the wrong number being quoted when you order replacement parts.

Typical Engine Identification Number



P Year of Manufacture



JS06050



Axle Serial Plate

The axle serial number is stamped on a plate mounted to the rear face of the axle.

- 1 When replacement parts are required, always ensure that the correct parts are obtained, e.g. in the case of gear replacements, always check the part number stamped on the gear, and the number of teeth.
- **2** When ordering replacement parts, quote the details on the serial plate as shown.



S156570

2 - 1

Torque Settings

2 - 1

Torque Settings

Note 1: The figures quoted are for non-plated fasteners and are to be used only when there is no torque setting specified in the relevant procedure in this service manual.

Note 2: The 4T grade settings DO NOT APPLY to fasteners used on the engine. If any 4T specification fasteners are found on the engine, these must be tightened to the figure quoted in the relevant engine manual.

Bolt Size	Strength Grade of Bolt or Stud											
	4T			8.8			10.9			12.9		
	Nm	kgf m	lbf ft	Nm	kgf m	lbf ft	Nm	kgf m	lbf ft	Nm	kgf m	lbf ft
МЗ	0.39	0.04	0.28	-	-	-	-	-	-	-	-	-
M4	0.78	0.08	0.57	-	-	-	-	-	-	-	-	-
M5	1.67	0.17	1.2	-	-	-	-	-	-	-	-	-
M6	2.84	0.29	2.1	8.04	0.82	5.9	11.3	1.15	8.3	-	-	-
M8	7.06	0.72	5.2	19.6	2.00	14.5	27.7	2.82	20.4	48.0	4.9	35
M10	14.0	1.43	10.3	39.1	3.99	28.8	55.0	5.61	40.6	94.0	9.6	69
M12	24.6	2.51	18.1	68.5	6.98	50.5	96.2	9.81	71	166	16.9	122
M16	61.9	6.31	45.7	173	17.6	127.6	242	24.7	178.5	400	40.8	295
M20	122	12.4	90	337	34.4	249	475	48.4	350	-	-	-
M22	167	17.0	123	464	47.3	342	652	66.5	481	-	-	-
M24	210	21.4	155	584	59.5	431	821	83.7	606	-	-	-
M27	311	31.7	229	864	88.1	637	1220	124	900	-	-	-
M30	420	42.8	310	1170	119	863	1650	168	1217	-	-	-
M33	576	58.7	425	1600	163	1180	2260	230	1667	-	-	-
M36	736	75.1	543	2050	209	1512	2880	294	2124	-	-	-
M39	961	98.0	709	2680	273	1977	3760	383	2773	-	-	-
M42	1190	121	878	3300	336	2434	4640	473	3422	-	-	-
M45	1490	152	1099	4140	422	3054	5820	593	4293	-	-	-
M48	1780	182	1312	4960	506	3659	6970	711	5141	-	-	-

* Note: All bolts are high tensile and must not be replaced by bolts of a lesser tensile specification.

Please Click Here To Download The Complete Manual Download Other Manuals If Having Any Questions Feel Free To Contact us

admin@servicemanualbit.com