HYDRAULIC EXCAVATOR

SHOP MANUAL

model SK60V

This is the shop manual for KOBELCO hydraulic excavator. Contained is the necesary technical data concerning the maintenance and repair of this model. The manual is divided into the following four major sections; GENERAL, SYSTEM, COMPONENTS and PROCEDURE.

* GENERAL

LE01. Specification

Operation (Refer to Operator's Manual)

LE03. Equipment layout and Weight

LE04. Maintenance standard and Test procedure

LE07. Working procedure

Preventive Maintenance (Refer to Operator's Manual)

LE08. Standard Flat rate table

* FACILITY

LE12. Hydraulic system LE15. Upper structure

LE18. Lower structure

LE21. Attachment

* EQUIPMENT

12. Pump

13. Control valve

14. Other valves

15. Motor

LE22. Control system

LE25. Electric system

LE26. Air conditioning system

LE29. Troubleshooting

16. Swivel joint

17. Cylinder

21. Reduction unit

50. Engine

* PROCEDURE

When checking or repairing the machine we suggest that you refer to this manual carefully. We hope that reference to this manual will help to maintain a high level of working efficiency and reliability. For further details on maintenance and checks refer to the "OPERATORS MANUAL" which has been supplied with the machine.

Although all data was correct at the time of printing, due to continual design changes and improvements, some contents may not conform to the actual machine. Take special care to order parts only after confirming the validity of the part number in the "PARTS MANUAL".

If you notice any explanatory discrepancies, after consulting one of our representatives, please update your manual according to the latest data. However, in the event of any specification changes, we will issue revised edition.

INDEX



SAFETY

WARNING

The proper and safe lubrication and maintenance for this machine, recommended by KOBELCO are outlined in the OPERATORS MANUAL for this machine.

Improper performance of lubrication or maintenance procedures is dangerous and could result in injury or death. Read and understand the OPERATORS MANUAL before performing any lubrication or maintenance.

The serviceman or mechanic may be unfamiliar with many of the systems on this machine. This makes it important to use caution when performing service work. A knowledge of the system and or components is important before the removal or disassembly of any component.

Because of the size of some of the machine components, the serviceman or mechanic should check the weights noted in this Manual. Use proper lifting procedures when removing any components.

Following is a list of basic precautions that should always be observed.

- Read and understand all Warning plates and labels on the machine before operating, lubricating or repairing this product.
- 2. Always wear protective glasses and protective shoes when working around machines. In particular, wear protective glasses when pounding on any part of the machine or its attachments with a hammer or sledge. Use welders gloves, hood/goggles, apron and other protective clothing appropriate to the welding job being performed. Do not wear loose-fitting or torn clothing. Remove all rings from fingers when working on machinery.
- Disconnect battery and discharge any capacitors before starting to work on machine. Hang "Do Not Operate" tag in the Operator's Compartment.
- 4. If possible, make all repairs with the machine parked on a level, hard surface. Block machine so it does not roll while working on or under machine.
- Do not work on any machine that is supported only by lift jacks or a hoist. Always use blocks or jack stands to support the machine before performing any disassembly.

WARNING

Do not operate this machine unless you have read and understand the instructions in the OPERATORS MANUAL. Improper machine operation is dangerous and could result in injury or death.

- 6. Relieve all pressure in air, oil or water systems before any lines, fittings or related items are disconnected or removed. Always make sure all raised components are blocked correctly and be alert for possible pressure when disconnecting any device from a system that untilizes pressure.
- 7. Lower the bucket, blade, ripper or other attachments to the ground before performing any work on the machine. If this cannot be done, make sure the bucket, blade, ripper or other attachments is blocked correctly to prevent it from dropping unexpectedly.
- 8. Use steps and grab handles when mounting or dismounting a machine. Clean any mud or debris from steps, walkways or work platforms before using. Always face machine when using steps, ladders and walkways. When it is not possible to use the designed access system, provide ladders, scaffolds, or work platforms to perform safe repair operations.
- 9. To avoid back injury, use a hoist when lifting components which weigh 23 kg (50 lbs) or more. Make sure all chains, hooks, slings, etc., are in good condition and are in the correct capacity. Be sure hooks are positioned correctly. Lifting eyes are not to be side loaded during a lifting operation.
- 10. To avoid burns, be alert for hot parts on machines which have just been stopped and hot fluids in lines, tubes and compartments.
- 11. Be careful when removing cover plates. Gradually back off the last two bolts or nuts located at opposite ends of the cover or device and pry cover loose to relieve any spring or other pressure, before removing the last two bolts or nuts completely.
- 12. Be careful when removing filler caps, breathers and plugs on the machine. Hold a rag over the cap or plug to prevent being sprayed or splashed by liquids under pressure. The danger is even greater if the machine has just been stopped because fluids can be hot.

M WARNING

- 13. Always use tools that are in good condition and be sure you understand how to use them before performing any service work.
- 14. Reinstall all fasteners with same part number. Do not use a lesser quality fastener if replacements are necessary.
- 15. Repairs which require welding should be performed only with the benefit of the appropriate reference information and by personnel adequately trained and knowledgeable in welding procedures. Determine type of metal being welded and select correct welding procedure and electrodes, rods or wire to provide a weld metal strength equivalent at least to that of parent metal. Always disconnect battery during welding operations to protect sensitive electric equipment.
- 16. Do not damage wiring during removal operations. Reinstall the wiring so it is not damaged nor will it be damaged in operation by contacting sharp corners, or by rubbing against some object or hot surface. Do not connect wiring to a line containing fluid.
- 17. Be sure all protective devices including guards and shields are properly installed and functioning correctly before starting a repair. If a guard or shield must removed to perform the repair work, use extra caution.
- 18. Loose or damaged fuel, lubricant and hydraulic lines, tubes and hoses can cause fires. Do not bend or strike high pressure lines or install ones which have been bent or damaged. Inspect lines, tubes and hoses carefully. Do not check for leaks with you hands. Pin hole (very small) leaks can result in a high velocity oil stream that will be invisible close to the hose. This oil can penetrate the skin and cause personal injury. Use cardboard or paper to locate pin hole leaks.
- 19. Tighten connections to the correct torque. Make sure that all heat shields, clamps and guards are installed correctly to avoid excessive heat, installed correctly to avoid excessive heat, vibration or rubbing against other parts during operation. Shields that protect against oil spray onto hot exhaust components in event of a line, tube or seal failure must be installed correctly.

- 20. Do not operate a machine if any rotating part is damaged or contacts any other part during operation. Any high speed rotating component that has been damaged or altered should be checked for balance before reusing.
- 21. On track-type machines, be careful when servicing or separating tracks. Chips can fly when removing or installing a track pin. Wear safety glasses and long sleeve shirts. Track can unroll very quickly when separated. Keep away from front and rear of machine. The machine can move unexpectedly when both tracks are disengaged from the sprockets. Block the machine to prevent it from moving.
- 22. Caution should be used to avoid breathing dust that may be generated when handling components containing asbestos fibers. If this dust is inhaled, it can be hazardous to your health. Components in KOBELCO products that may contain asbestos fibers are brake pads, brake band and lining assemblies, clutch plates and some gaskets. The asbestos used in these components is usually bound in a resin or sealed in some way. Normal handling is not hazardous as long as airborne dust which contains asbestos is not generated.

If dust which may contain asbestos is present, there are several common sense guidelines that should be followed.

- a. Never use compressed air for cleaning.
- Avoid brushing or grinding of asbestos containing materials.
- c. For clean up, use wet methods or a vacuum equipped with a high efficiency particulate air (HEPA) filter.
- d. Use exhaust ventilation on permanent machining jobs.
- e. Wear and approved respirator if there is no other say to control the dust.
- f. Comply with applicable rules and regulations for the work place.
- g. Follow environmental rules and regulations for disposal of asbestos.
- Avoid areas where asbestos particles may be in the air.

SHOP MANUAL

model SK60V

CONTENTS

1. SPECIFICATION	LE01
2. OPERATION (Refer to Operators Manual)	
3. EQUIPMENT LAYOUT AND WEIGHT	LE03
4. MAINTENANCE STANDARDS AND TEST PROCEDURE	LE04
6. PREVENTIVE MAINTENANCE (Refer to Operators Manual)	
7. WORK STANDARD	LE07
8. STANDARD FLAT RATE TABLE	LE08

* How to index sections in this manual
The general section in this manual is composed of 7 chapters
as shown above, and every chapter can be indexed easily using
the marks on the edge. This is useful for rapid reference.


△ WARNING

The proper and safe lubrication and maintenance for this machine, recommended by KOBELCO are outlined in the OPERATORS MANUAL for this machine.

Improper performance of lubrication or maintenance procedures is dangerous and could result in injury or death. Read and understand the OPERATORS MANUAL before performing any lubrication or maintenance.

⚠ WARNING

Do not operate this machine unless you have read and understand the instructions in the OPERATORS MANUAL. Improper machine operation is dangerous and could result in injury or death.





GENERAL

SK060 SK70 SK60

List of General Section in Manual

Class	ss Name		Book code No.	
Ciass		Distribution date		
LE01	SPECIFICATION	S5LE0106E 1994-07		
	OPERATION	S2LE1016E Refer to Operators manual		
LE03	EQUIPMENT LAYOUT AND WEIGHT	S5LE0306E 1994 — 07		
LE04	MAINTENANCE STANDARDS AND TEST PROCEDURES	S5LE0407E 1994 — 07		
. —	PREVENTIVE MAINTENANCE	S2LE1016E Refer to Operators manual		
LE07	WORK STANDARD	S5LE0703E 1994—07		
LE08	STANDARD FLAT RATE TABLE	S5LE0803E 1994 — 07		
		3		
,				
				-
	Applicable Machine	LE-17701~		

KOBELCO

SHOP MANUAL



SPECIFICATION

LE01

CONTENTS

1.	DESIGNATION	1
2.	GENERAL DIMENSION	2
3.	SPECIFICATION AND PERFORMANCE	3
4.	TYPE OF SHOES	4
5.	TYPE OF BUCKETS ·····	5
6.	COMBINATION OF ATTACHMENTS	6
7.	WORKING RANGE OF ATTACHMENTS	7
8.	LIFTING CAPACITY DIAGRAM	9
9.	ENGINE SPECIFICATION	11

Applicable machine LE-17701~

Revisions	Print date	Remarks
First edition	July, 1994	S5LE0106E Y.G
-		

Please Click Here To Download The Complete Manual Download Other Manuals If Having Any Questions Feel Free To Contact us

admin@servicemanualbit.com